



# Full Color Ceiling Panel

FilaSorb™ 24

acoufelt  
making quiet

# Product Detail

|                  |                |
|------------------|----------------|
| Application      | Ceiling        |
| Composition      | 100% polyester |
| Material         | FilaSorb™      |
| Recycled content | 60% min        |
| Dimensions       | 1200 x 2780mm  |
| Thickness        | 24mm +/- 10%   |

# Guarantees

|                          |           |
|--------------------------|-----------|
| Warranty against defects | 20 years* |
| Color fastness warranty  | 20 years* |

\*conditions apply

# QuickShip

QuickShip Standard (Made to Order)



Our standard made to order products have an approx. **2–3 week** lead time from payment and order confirmation.

# Technical Data

|                    |  |
|--------------------|--|
| Fire rating        | AS/ISO 9705.1, Group 1<br>ASTM E84-17a, Class A<br>EN 13501-1: 2019, B-s1, d0          |
| Indoor air quality | SCS-EC10.3-2014 v4.0 meeting standard CDPH/EHLB Standard Method v.1.2-2017, ≤ 0.5mg/m³ |
| Color fastness     | ISO 105-B02, 6-7   |

# Sustainability



Made from 60% min. recycled content



Red List Free Declare Label (3<sup>rd</sup> Party Verified)



Generated using 40% solar energy



Recyclable at end-of-life



Total VOC's less than 0.5 mg/m³ (3<sup>rd</sup> Party Verified)




Phenol & formaldehyde free



# Acoustic Performance

|             |                       |
|-------------|-----------------------|
| Test method | ISO 354-2006          |
| Results     | NRC 0.60 (no air gap) |



| Frequency (Hz) | 125  | 250  | 500  | 1000 | 2000 | 4000 | NRC  |
|----------------|------|------|------|------|------|------|------|
| α <sub>s</sub> | 0.02 | 0.57 | 0.41 | 0.58 | 0.87 | 0.85 | 0.60 |


# Colorways

Light Reflectance Values (LRV), are a measure of the percentage of visible and usable light that is reflected from a surface when illuminated by a light source.


|   |   |   |  |   |   |   |   |   |   |   |
|---|---|---|--|---|---|---|---|---|---|---|
|    |    |    |    |    |    |    |    |    |    |    |
| Celery<br>LRV – 43.64%  | Flint<br>LRV – 5.14%  | Shiraz<br>LRV – 3.99%   | Quartz<br>LRV – 36.85%   | Peppercorn<br>LRV – 8.50%   | Currant<br>LRV – 7.04%  | Carrot<br>LRV – 20.00%  | Peach<br>LRV – 29.00%   | Flamingo<br>LRV – 37.54%  | Turmeric<br>LRV – 29.59%  | Popcorn<br>LRV – 65.00%   |
|   |   |   |   |   |   |   |   |   |   |   |
| Kale<br>LRV – 4.50%   | Oregano<br>LRV – 8.80%  | Thistle<br>LRV – 13.00%   | Wasabi<br>LRV – 38.00%   | Sencha<br>LRV – 34.15%  | Pistachio<br>LRV – 30.00%   | Midnight Blue<br>LRV – 3.50%  | Granite<br>LRV – 6.40%  | Denim<br>LRV – 6.00%  | Peacock<br>LRV – 19.00%   | Azur<br>LRV – 18.00%  |
|  |  |  |  |  |  |  |  |  |  |  |
| Marine<br>LRV – 25.00%  | Periwinkle<br>LRV – 36.00%  | Sea Salt<br>LRV – 28.56%  | Lilac<br>LRV – 39.00%  | Iris<br>LRV – 10.50%  | Berry<br>LRV – 12.00%   | Piano Black<br>LRV – 3.00%  | Charcoal<br>LRV – 5.46%   | Slate<br>LRV – 12.50%   | Grey<br>27.00%  | Metal<br>LRV – 35.00%   |
|  |  |  |  |  |  |  |  |  |   |   |
| Platinum<br>LRV – 42.00%  | Walnut<br>LRV – 12.14%  | Umber<br>LRV – 20.35%   | Almond<br>LRV – 53.64%   | Ivory<br>LRV – 40.00%   | Pearl<br>LRV – 54.00%   | White<br>LRV – 83.22%   | Lipstick Red<br>LRV – 12.50%  | Butter<br>LRV – 62.00%  |   |   |

# Mounting Methods

## Adhesive Method




----- Panel installation area  
——— Construction adhesive




----- Panel installation area  
~~~~~ Spray adhesive

## Disc Magnet Method




□ Metal mounting plate attached to panel

### Side view




### Disc Magnet




HOLD 5kg

## Pot Magnet Method




□ Metal mounting plate attached to panel

### Side view




### Pot Magnet




HOLD 14kg


## Channel Mount Method



⊙ Magnets



### Pot Magnet



HOLD 14kg