

Urban

QuietBackTM Carpet Tiles



Product Detail

Application Floor

Composition QuietBack™

Material100% solution dyed nylonStyleMulti-level textured loop pileRecycled contentBacking made from >80%

Backing made from >80% recycled PET

Tile dimensions500 x 500mmThickness10mm +/- 10%

Tiles per box 20


Guarantees

Wear warranty 20 years*
Castor chair proof 20 years*
Anti-static Lifetime*
Colorfast 20 years*

Classification Commercial Extra Heavy Duty

*conditions apply

Installation Method



Technical Data

Dimensional stabilityISO 17984, -0.05%Electrostatic propensityAATCC 134, < 0.70 kW</th>Color fastnessISO 105-B02, 6-7

Thermal resistance 0.2m² K/W

Fire test method AS/ISO 9239.1-2003
Critical heat flux Mean result 7.4kW/m²
Smoke deviation rate Mean result 175%.min

Fire test method ASTM E648
Classification Class 1

Critical heat flux Average, 0.54kWm²

Smoke density test method ASTM E662 (Flaming)


Smoke density test rate 450 or less
Fire test method EN ISO 9239

Critical heat fluxCflSmoke deviation rate\$1

Antimicrobial effectiveness AATTCC Method 174:2016

Part II, <100

Acoustic Performance



Frequency (Hz)	125	250	500	1000	2000	4000	NRC
αs	0.01	0.08	0.40	0.41	0.46	0.55	0.40

Sustainability



Backing made from 80% min. recycled content



Red List Free
Declare Label
(3rd Party Verified)





formaldehyde free



Total VOC's less than 0.5 mg/m³ (3rd Party Verified)







QuickShip

QuickShip Rapid



QuickShip Rapid products can be despatched within **1-2 days**.



Colorways



Singapore Plaza LRV – 3.72%



Sydney Harbour LRV – 3.73%



Manhattan Sidewalk LRV – 4.22%

